

TECHNICAL DATA SHEET

CHALKBOARD PAINT

- Write, draw, erase
- Easy application
- Excellent coverage
- Abrasion resistant

Colour: Black

Effect: Matt

Capacity: 750 ml

BLACKBOARD PAINT is an innovative product based on aqueous acrylic dispersion, characterized by a matte finish. It creates a blackboard-like surface where you can write and draw with chalk and then easily wipe off with a wet cloth or sponge. It is versatile, abrasion-resistant, efficient and quick-drying, which makes application easy and the effect durable.

BLACKBOARD PAINT is intended for protective and decorative finishing of surfaces inside rooms and painting various surfaces, such as walls, wood, MDF, etc.

BLACKBOARD PAINT provides creative fun, easy exchange of information, the ability to write and draw with chalk, and the organization of daily activities. It is ideal for use in the kitchen, restaurant, lecture hall, school, children's room and anywhere where creative use of space is required.

SUBSTRATE PREPARATION:

- › The surface to be painted should be dry, clean, degreased and matted with sandpaper and then dust-free.
- › In renovation painting, old peeling coatings should be removed. Fill any cavities and cracks with an appropriate putty, and after drying, sand thoroughly with sandpaper, and then remove dust.
- › If it is necessary to strengthen the substrate, use the GRUNT primer.
- › Protect non-paintable surfaces from possible dirt with painter's tape.

HOW TO USE:

- › Mix the paint thoroughly immediately before painting and before applying the next layer. Do not dilute.
- › Apply the first layer of paint to the previously prepared surface with a brush or roller, spreading thoroughly until an even layer is obtained and waiting for drying.
- › After the first layer has dried, apply the same layers of paint until the desired effect is achieved. It is recommended to make 2 to 3 layers.
- › The drying time of the coating is about 2 hours and depends on the conditions at the place of application of the product (temperature and humidity).

TECHNICAL DATA SHEET

CHALKBOARD PAINT

ADDITIONAL INFORMATION:

- › Optimal application conditions: temperature from +10°C to +30°C and relative humidity below 70%.
- › Initial surface protection after 24 hours. The coating is completely durable after 7 days, until then do not clean the painted surface, protect against water and dirt and mechanical damage.
- › Mild detergents should be used to care for the painted surface. Do not use rough sponges.
- › Wash the tools with water and detergent immediately after painting.

EFFICIENCY:

- › Up to 12 m²/l, depending on the type of substrate and method of application. Performance for a single layer.

NUMBER OF LAYERS:

- › 2 to 3 layers, depending on the type of substrate and the desired effect.

SHELF LIFE:

- › 36 months from the date of production. Once opened, use within 6 months.

TRANSPORT AND STORAGE:

- › Store and transport in airtight, original packaging at a temperature of +5°C to +40°C. Protect from frost.

COMMENTS:

- › Keep out of reach of children.
- › If swallowed, consult a doctor.
- › VOC content limit (cat. A/a/WB): 30 g/l. The product contains max. 30 g/l.
- › It contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction.
- › Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.