

TECHNICAL DATA SHEET

CONCRETE-FLOOR PAINT

- One-component
- Protects and decorates
- Excellent coverage
- Durable coating

Colour: brick red, chocolate, ash, steel

Effect: Matt

Capacity: 800 ml

CONCRETE-FLOOR PAINT is a water-based acrylic paint created specifically for painting floors and other concrete surfaces. Its matte finish provides a modern look while emphasizing the natural character of concrete. Thanks to its innovative formula and the highest quality raw materials, the paint guarantees excellent adhesion to the substrate and perfect coverage, which makes painting easy and effective. Abrasion resistance makes surfaces painted with paint not only aesthetically pleasing, but also long-lasting and easy to maintain. In addition, the paint protects and decorates, giving concrete floors a new, attractive look. Its resistance to dirt and weather conditions make it suitable for both indoor and outdoor use, in areas with moderate pedestrian and vehicular traffic.

Decorative and protective painting:

- ✓ Concrete floors and screeds
- ✓ Terraces and balconies
- ✓ Fences and concrete structures
- ✓ Garden walkways
- ✓ New and renovated concrete surfaces

SUBSTRATE PREPARATION:

- › The surface to be painted should be seasoned, degreased, clean and dry.
- › Mechanically troweled concrete and smooth, compact surfaces should be roughened to ensure adequate adhesion of the coating.
- › In renovation painting, remove old coatings, fill in cavities, clean from impregnation and then sand the surface and remove dust.
- › In order to reduce absorbency, prime the substrate with GRUNT primer.
- › In order to obtain proper adhesion of the paint, before applying the next layer, the dried surface should be sanded with fine-grained sandpaper and then dedusted.

HOW TO USE:

- › Mix the product thoroughly immediately before painting. Do not dilute.
- › Apply the first layer of paint to the previously prepared surface with a brush, roller or spray, spreading thoroughly until an even layer is obtained and waiting for the coating to dry.

TECHNICAL DATA SHEET

CONCRETE-FLOOR PAINT

- › After the first layer has dried, apply the second layer of paint in the same way until the desired effect is achieved.
- › Substrates particularly exposed to abrasion should be covered with three layers of paint.
- › The drying time of the coating is about 4 hours and depends on the conditions at the place of application of the product (temperature and humidity).

ADDITIONAL INFORMATION:

- › Optimal application conditions: temperature from +10°C to +30°C and relative humidity below 70%.
- › Initial surface protection after 24 hours. The coating is completely durable after 7 days, until then do not clean the painted surface, protect against water and dirt and mechanical damage.
- › Mild detergents should be used to care for the painted surface. Do not use rough sponges.
- › Wash the tools with water and detergent immediately after painting.

EFFICIENCY:

- › Up to 12 m²/l, depending on the type of substrate and method of application. Efficiency given for one layer.

NUMBER OF LAYERS:

- › 2 to 3 layers, depending on the type of substrate and the desired effect.

SHELF LIFE:

- › 36 months from the date of production. Once opened, use within 6 months.

TRANSPORT AND STORAGE:

- › Store and transport in airtight, original packaging at a temperature of +5°C to +40°C. Protect from frost.

COMMENTS:

- › Keep out of reach of children.
- › If swallowed, consult a doctor.
- › VOC content limit (cat. A/i/WB): 140 g/l. The product contains max. 140 g/l.
- › It contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction.
- › Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.