

Update date: 22.04.2024 Version: 3.0/EU

# TECHNICAL DATA SHEET GLAMOR effect GLAZE

- ➤ One-component
- Protects and decorates
- ➤ Abrasion resistant
- > Protection against moisture and dirt
- Lamperie varnish

Colour: Clear

Effect: Gloss, Matt Capacity: 750 ml

**GLAMOR effect GLAZE** is a unique product that combines a protective and decorative function, allowing for easy and effective finishing of various interior surfaces. It creates a durable abrasion-resistant coating and provides protection against dirt and moisture, which makes it easier to keep clean and prevents damage to the surface. Thanks to the choice of gloss or matte effect, you can achieve a variety of decorative effects. The wood stain can be used alone or in combination with the decorative effects GLAMOUR effect Metallic Glow or Moondust, giving the surfaces a unique look. This product is also suitable for varnishing wood and wood-based materials used indoors. In addition, it can be used together with the coloured STAIN VARNISH product as an additional finishing layer, providing even greater protection and durability. Thanks to its versatility and ease of use, Lazura can be used for a variety of finishing projects, creating interiors full of style and elegance.

#### **HOW TO USE:**

- > The surface to be painted should be seasoned, degreased, clean and dry.
- > Mix the product thoroughly immediately before painting. Do not dilute.
- > Apply a layer of wood stain to the previously prepared surface using a short-pile roller dedicated to varnishes, thoroughly spreading it on the surface from bottom to top until an even layer is obtained and wait for the coating to dry.
- > When applying the stain with a brush or sponge, apply it to the surface unevenly, "spot-like", with irregular movements, leaving free (unpainted) areas, which should be gradually filled in until the entire surface is covered and left to dry.
- The drying time of the coating is about 2 hours and depends on the conditions at the place of application of the product (temperature and humidity).

### **DECORATIVE EFFECTS**

- ✓ To create a metallic glow, add 80 ml of GLAMOUR effect Metallic Glow to 750 ml of GLAMOUR effect GLAZE and mix thoroughly until a homogeneous mass is obtained. Apply in the same way as the stain itself.
- $\checkmark$  To obtain the sparking effect, add 10 g to 70 g of GLAMOUR effect Moondust to 750 ml of GLAMOUR effect GLAZE and mix thoroughly until a homogeneous mass is obtained. Apply in the same way as the stain itself.

Update date: 22.04.2024 Version: 3.0/EU

# TECHNICAL DATA SHEET GLAMOR effect GLAZE

✓ GLAMOUR effect GLAZE can also be coloured with PIGMENT MIX pigment concentrate to obtain a coloured transparent coating. To 750 ml of GLAMOUR effect GLAZE add max. 80 ml PIGMENT MIX and mix thoroughly until a homogeneous mass is obtained. Apply in the same way as the stain itself.

#### **ADDITIONAL INFORMATION:**

- > Optimal application conditions: temperature from +10°C to +30°C and relative humidity below 70%.
- > Initial surface protection after 24 hours. The coating is completely durable after 7 days, until then do not clean the painted surface, protect against water and dirt and mechanical damage.
- > Mild detergents should be used to care for the painted surface. Do not use rough sponges.
- > Wash the tools with water and detergent immediately after painting.

#### **EFFICIENCY:**

> Up to 20 m<sup>2</sup>/l, depending on the type of substrate and the method of application.

#### **NUMBER OF LAYERS:**

> 1 layer.

#### **SHELF LIFE:**

> 36 months from the date of production. Once opened, use within 6 months.

### TRANSPORT AND STORAGE:

> Store and transport in airtight, original packaging at a temperature of +5°C to +40°C. Protect from frost.

### **COMMENTS:**

- > Keep out of reach of children.
- > If swallowed, consult a doctor.
- > VOC content limit (cat. A/e/WB): 130 g/l. The product contains max. 130 g/l.
- > It contains 1,2-benzoisothiazol-3(2H)-one. May cause an allergic reaction.
- > Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.