

TECHNICAL DATA SHEET

LAMPERY VARNISH

- Professional
- Clear acrylic lacquer
- Fast drying
- Scrub resistance
- Easy application

Colour: Clear

Effect: satin, matt

Capacity: 2.5 L; 5 L

LAMPERY VARNISH is a colourless, ecological acrylic varnish, developed on the basis of water-soluble components, which provides a durable, non-absorbent coating with high aesthetic values. The product is perfect for interior walls covered with scrub-resistant paints, guaranteeing colour and surface protection against water and daily wear and tear. Thanks to its modern formula, the lacquer is solvent-free, odourless, quick-drying and environmentally friendly. The lacquer formula has been developed for ease of application, and the thixotropic texture prevents dripping, which makes the product perfect for painting vertical surfaces. The lacquer forms a smooth, water- and cleaner-resistant coating that does not turn yellow, maintaining a long-lasting aesthetic effect and allowing easy cleaning. The product is scratch resistant, which ensures a durable finish on usable surfaces. Thanks to its outstanding performance, the lacquer allows for economical application, effectively decorating and protecting larger surfaces.

HOW TO USE:

- › The surface to be painted should be seasoned, degreased, clean and dry.
- › Mix the product thoroughly immediately before painting. Do not dilute.
- › Apply a layer of varnish to the previously prepared surface using a short-pile roller dedicated to varnishes, spreading it thoroughly on the surface from bottom to top until an even layer is obtained and wait until the coating dries.
- › The drying time of the coating is about 2 hours and depends on the conditions at the place of application of the product (temperature and humidity).

ADDITIONAL INFORMATION:

- › Optimal application conditions: temperature from +10°C to +30°C and relative humidity below 70%.
- › Initial surface protection after 24 hours. The coating is completely durable after 7 days, until then do not clean the painted surface, protect against water and dirt and mechanical damage.
- › Mild detergents should be used to care for the painted surface. Do not use rough sponges.
- › Wash the tools with water and detergent immediately after painting.

TECHNICAL DATA SHEET

LAMPERY VARNISH

EFFICIENCY:

- › Up to 20 m²/l, depending on the type of substrate and the method of application.

NUMBER OF LAYERS:

- › 1 layer.

SHELF LIFE:

- › 36 months from the date of production. Once opened, use within 6 months.

TRANSPORT AND STORAGE:

- › Store and transport in airtight, original packaging at a temperature of +5°C to +40°C. Protect from frost.

COMMENTS:

- › Keep out of reach of children.
- › If swallowed, consult a doctor.
- › VOC content limit (cat. A/e/WB): 130 g/l. The product contains max. 130 g/l.
- › It contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction.
- › Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.