

TECHNICAL DATA SHEET

MARKERMIX

- Easy application
- Excellent coverage
- Colour fastening
- Fast drying
- UV protection

Colour: Black, Silver, Old Gold, Gold

Effect: Satin

Capacity: 15 ml

MARKERMIX is a versatile product whose formula is based on aqueous acrylic resin and special effect pigments. Thanks to the careful selection of ingredients, this lacquer is characterized by exceptional durability and resistance to external conditions, making it an ideal solution for both interior and exterior applications. It is characterized by very good adhesion to various substrates and resistance to scrubbing and weather conditions, which makes the coating formed by the varnish durable and resistant to external conditions. In addition, it is waterproof and has a neutral odour, which makes it user-friendly. **MARKERMIX** is a great solution for many applications, including painting Christmas decorations, decorating glass, renovating picture frames, painting and restoring tombstone letters, and many other decorative works. Its unique marker design allows you to comfortably use two nibs: a thin one for precise application of small details and a brush for thicker lines. This makes lacquer an indispensable tool for those looking for both precision and convenience in decorative work.

HOW TO USE:

- › The surface to be painted should be dry, clean and free of grease. Before painting, it is essential to remove all dirt, greasy stains and remains of old coatings.
- › Mix the product thoroughly immediately before painting. Do not dilute. Always perform a test on the ground.
- › The substrate should be painted with a brush, roller or sponge. Stir the varnish frequently during painting.
- › Depending on the desired effect, apply 1 or 2 coats of polish.
- › The drying time is about 2 hours and depends on the conditions at the place of application of the product (temperature and humidity).

TECHNICAL DATA SHEET

MARKERMIX

ADDITIONAL INFORMATION:

- › Optimal application conditions: temperature from +10°C to +30°C and relative humidity below 70%.
- › Initial surface protection after 24 hours. The coating is completely durable after 7 days, until then do not clean the painted surface, protect against water and dirt and mechanical damage. Until then, do not clean the painted surface, protect it from water and dirt as well as mechanical damage.
- › Wash the tools with water and detergent immediately after painting.

EFFICIENCY:

- › Up to 10 m²/l, depending on the type of substrate and method of application. Efficiency given for one layer.

NUMBER OF LAYERS:

- › 1 to 2 coats, depending on the type of substrate and the desired effect.

SHELF LIFE:

- › 36 months from the date of production. Once opened, use within 6 months.

TRANSPORT AND STORAGE:

- › Store and transport in airtight, original packaging at a temperature of +5°C to +40°C. Protect from frost.

COMMENTS:

- › Keep out of reach of children.
- › If swallowed, consult a doctor.
- › VOC content limit (cat. A/d/WB): 130 g/l. The product contains max. 130 g/l.
- › It contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction.
- › Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.