

## TECHNICAL DATA SHEET

### MIXSTONE PROFESSIONAL VARNISH

- Painting and renovation
- Excellent coverage
- Colour fastening
- Fast drying
- UV protection

**Colour:** Black, Silver, Gold

**Effect:** Satin

**Capacity:** 80 ml, 300 ml

**MIXSTONE PROFESSIONAL VARNISH** is a high-quality product designed for professional use both indoors and outdoors. Its formula is based on water, acrylic resin and effect pigments, which guarantees excellent results and durability. It has very good adhesion to a wide variety of substrates, which makes it ideal for painting and renovating letters on tombstones and for creating decorations and patterns on stone substrates such as marble, granite, sandstone or terrazzo. Thanks to its special formula, the lacquer creates a coating resistant to scrubbing and scratches, which ensures a long-lasting aesthetic effect. It is also waterproof and resistant to weather conditions, which means that it retains its properties even in difficult outdoor conditions. An additional advantage of the product is its neutral smell, which makes its application comfortable for the user. MIXSTONE PROFESSIONAL VARNISH is not only excellent surface protection, but also the ability to create beautiful and durable decorations on a variety of stone materials.

#### HOW TO USE:

- › The surface to be painted should be dry, clean and free of grease. Before painting, it is essential to remove all dirt, greasy stains and remains of old coatings.
- › Mix the product thoroughly immediately before painting. Do not dilute. Always perform a test on the ground.
- › The substrate should be painted with a brush, roller or sponge. Stir the varnish frequently during painting.
- › Depending on the desired effect, apply 1 or 2 coats of polish.
- › The drying time is about 2 hours and depends on the conditions at the place of application of the product (temperature and humidity).

#### ADDITIONAL INFORMATION:

- › Optimal application conditions: temperature from +10°C to +30°C and relative humidity below 70%.

## TECHNICAL DATA SHEET

### MIXSTONE PROFESSIONAL VARNISH

- › Initial surface protection after 24 hours. The coating is completely durable after 7 days, until then do not clean the painted surface, protect against water and dirt and mechanical damage. Until then, do not clean the painted surface, protect it from water and dirt as well as mechanical damage.
- › Wash the tools with water and detergent immediately after painting.

**EFFICIENCY:**

- › Up to 10 m<sup>2</sup>/l, depending on the type of substrate and method of application. Efficiency given for one layer .

**NUMBER OF LAYERS:**

- › 1 to 2 coats, depending on the type of substrate and the desired effect.

**SHELF LIFE:**

- › 36 months from the date of production. Once opened, use within 6 months.

**TRANSPORT AND STORAGE:**

- › Store and transport in airtight, original packaging at a temperature of +5°C to +40°C. Protect from frost.

**COMMENTS:**

- › Keep out of reach of children.
- › If swallowed, consult a doctor.
- › VOC content limit (cat. A/d/WB): 130 g/l. The product contains max. 130 g/l.
- › It contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction.
- › Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.