

TECHNICAL DATA SHEET

PIGMENT MIX-BUDmax

- Waterborne
- Wide range of colours
- Easy to use
- UV resistant
- For dispersion paints and plasters as well as decorative concretes

Colour: Blue, Brown, Dark brown, Peach, Lemon, Chocolate, Black, Red, Caramel, Forest, Raspberry, Mint, Apricot, Camo, Olive, Orange, Sand, Pistachio, Sunny, Turquoise, Stall, Heather, Green, Yellow

Capacity: 500 ml

PIGMENT MIX-BUDmax is a high-quality pigment concentrate in the form of an aqueous dispersion of pigments, enriched with dispersing and wetting agents and viscosity regulators. The safe composition is free of resins, ethylene glycol, heavy metals and volatile organic compounds. The product is intended for use in dispersion paints and plasters as well as decorative concretes, characterized by resistance to UV rays and durability. The formula is based on carefully selected inorganic and organic pigments, ensuring maximum resistance to light, weathering and alkaline environments, lime and cement. PIGMENT MIX-BUDmax provides repeatable and cost-effective solutions, and each concentrate undergoes detailed quality control to guarantee colour accuracy and repeatability. It is available in a wide range of colours, and the possibility of mixing concentrates allows you to create your own colours. The product spreads perfectly in dispersion paints and plasters, as well as in concrete decorative materials, ensuring a durable and even colouring effect. It is suitable for use in paints and plasters for both interior and exterior applications. It can also be used to colour in the mass of products containing cement or lime. In addition, it is compatible with other products of the brand, such as GROUT RENOVATOR, PRIMER and GLAMOR effect GLAZE.

HOW TO USE:

- › Before application, the PIGMENT MIX-BUDmax concentrate should be mixed thoroughly. Possible delamination is not a defect of the product.
- › A test should be performed on a small amount of the coloured product in order to check the mutual tolerance and determine the appropriate proportion.
- › Slowly pour the required amount of concentrate into the coloured product, stirring thoroughly manually or mechanically, until a uniform colour is obtained. Excessive foaming should be avoided during mixing, which may impair application properties.
- › A maximum addition of 5% of PIGMENT MIX-BUDmax concentrate is recommended for the total weight of the coloured product.

TECHNICAL DATA SHEET

PIGMENT MIX-BUDmax

ADDITIONAL INFORMATION:

- › It is recommended to carry out a colouring test on a smaller amount of paint or plaster due to the diversity of technologies and raw materials used by different manufacturers.
- › The colours presented on the sample book are illustrative, the colours obtained may vary depending on the type and quality of the coloured product.
- › Absorbency, type and structure of the substrate, ambient conditions and lighting can all affect the final colour. It is recommended to take these factors into account when choosing a colour.
- › Avoid using PIGMENT MIX-BUDmax for colouring mineral paints and plasters in dark and intense colours.
- › Do not use the following colours for silicate paints: Peach, Raspberry, Heather, Green and Blue.
- › In products containing cement or lime coloured in the mass, salt efflorescence may be formed due to the maturation of the cement-lime mortar, and not to the addition of the pigment concentrate itself. If efflorescence appears, it should be removed gently with a soft brush. The use of chemicals to clean the eruptions can aggravate the discoloration.
- › Wash the tools with water and detergent immediately after colouring.

SHELF LIFE:

- › 36 months from the date of production. Once opened, use within 6 months.

TRANSPORT AND STORAGE:

- › Store and transport in airtight, original packaging at a temperature of +5°C to +40°C. Protect from frost.

COMMENTS:

- › Keep out of reach of children.
- › If swallowed, consult a doctor.
- › It contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction.
- › Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.