

## TECHNICAL DATA SHEET

### WALLPAPER ADHESIVE STRONG

- For glass fibre wallpaper
- Excellent adhesion
- Ready to use
- Easy application

**Weight:** 1kg; 2.5kg

**WALLPAPER ADHESIVE STRONG** is a ready-to-use product, ideal for fiberglass wallpapers and heavy wallpapers with a weight of over 420 g/m<sup>2</sup>. It provides a durable and very strong connection between wallpaper and photo wallpaper and wall murals. The joint becomes transparent after drying, which guarantees an aesthetic finish. This adhesive is suitable for use on lime-cement plasters and drywall indoors. Before you start wallpapering, read the recommendations of the wallpaper manufacturer.

#### SUBSTRATE PREPARATION:

- › The surface to be wallpapered should be dry, clean, smooth, absorbent and durable.
- › Remove all roughness, residues of adhesive paints and wallpapers from the surface.
- › In the case of crumbling substrates, remove unstable parts of the substrate and fill in any cavities.
- › If the surfaces are highly absorbent, prime using PRIMER or WALLPAPER ADHESIVE STRONG diluted with water (max. 10% water) and then leave to dry.

#### HOW TO USE:

- › The adhesive should be mixed thoroughly before use.
- › Apply the adhesive with a roller or brush to the cleaned and prepared surface of the wall to be wallpapered.
- › Brush the wallpaper pieces with glue, fold them inwards so that the wallpaper soaks up the glue.
- › In the case of non-woven wallpapers, apply dry wallpaper to a previously glued wall.
- › Glue strips of wallpaper (panels) edge-to-edge.
- › Tighten the joints of the belts (panels) carefully with a roller.
- › Remove excess glue with a damp cloth or sponge.

#### ADDITIONAL INFORMATION:

- › Optimal application conditions: temperature from +5°C to +25°C and relative humidity below 70%.
- › Follow the instructions and recommendations of the wallpaper manufacturer as to how to glue it.
- › Wash the tools with warm water and detergent immediately after wallpapering

#### EFFICIENCY:

- › Up to 6 m<sup>2</sup>/kg, depending on the absorbency of the substrate and the type of wallpaper.

# TECHNICAL DATA SHEET

## WALLPAPER ADHESIVE STRONG

**SHELF LIFE:**

- › 24 months from the date of production. Once opened, use within 14 days.

**TRANSPORT AND STORAGE:**

- › Store and transport in airtight, original packaging at a temperature of +5°C to +25°C.
- › Store in a dark and dry place.

**COMMENTS:**

- › Keep out of reach of children.
- › If swallowed, consult a doctor.
- › The device has been treated with a biocidal product. Contains C(M)IT/MIT (3:1). It contains a reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 1,2-benzisothiazole 3(2H)-one. May cause an allergic reaction.
- › Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.