

## TECHNICAL DATA SHEET

### WALLPAPER REMOVAL FLUID

- For all types of wallpapers
- High performance
- Easy application
- Contains silver ions

**Capacity:** 500 ml

**WALLPAPER REMOVAL FLUID** is designed for easy and effective removal of wallpaper from various materials, including glass fibre wallpaper, fabric wallpaper, PVC wallpaper, natural and synthetic fibre wallpaper, paper wallpaper, photo wallpaper and vinyl wallpaper on a paper or textile substrate. The product is also perfect for removing adhesive paints. Thanks to its advanced formula, the liquid allows you to quickly and effectively remove various types of wallpaper without damaging the substrate. The product stands out for its versatility, effectiveness and safety. The agent is easily biodegradable and does not pose a threat to the environment. It is suitable for a variety of wallpaper types and substrates, allowing you to remove wallpaper quickly and effectively without damaging the surface. In addition, the silver ions contained in the product have antibacterial and antifungal properties, preventing the growth of fungi and bacteria on the cleaned surface.

#### HOW TO USE:

- › Dilute the contents of the package in 25-30 l of paper wallpaper remover, 15-20 l of thick or heavy wallpaper remover, 30 l of adhesive paint remover.
- › Apply the solution generously to the wallpaper to be removed with a sponge, brush or roller.
- › Before applying the solution to vinyl, washable or lacquered wallpaper, cut the wallpaper, wipe it with coarse sandpaper or puncture it with a special needle roller to give the fluid access to the bottom of the wallpaper.
- › Moisture-sensitive surfaces such as floors and doors should be protected with foil, for example.

#### ADDITIONAL INFORMATION:

- › Optimal application conditions: temperature from +5°C to +25°C and relative humidity below 70%.
- › Wash the tools with warm water and detergent immediately after work.

#### EFFICIENCY:

- › Up to 200 m<sup>2</sup>/l, depending on the type of wallpaper.

#### SHELF LIFE:

- › 24 months from the date of production.

## TECHNICAL DATA SHEET

### WALLPAPER REMOVAL FLUID

**TRANSPORT AND STORAGE:**

- › Store and transport in airtight, original packaging at a temperature of +5°C to +30°C.
- › Protect from frost and sunlight.
- › Close tightly after opening.

**COMMENTS:**

- › Keep out of reach of children.
- › If swallowed, consult a doctor.
- › Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.