

TECHNICAL DATA SHEET

WOOD STAIN

- Protects and decorates
- Colour fastening
- Fast drying
- Universal
- UV protection

Colour: White, Oak, Fir, Rosewood, Pine, Golden Pine, Gray, Teak, Venge

Effect: Satin

Capacity: 900 ml

WOOD STAIN is a high-quality product that is perfect for decorating and protecting various wooden and wood-based surfaces, such as fences, facades, furniture, gazebos, paneling, etc. This product has been specially developed for both indoor and outdoor use. The stain varnish is a multi-purpose product that not only gives an aesthetic appearance to wooden surfaces, but also provides them with effective protection against various external factors.

- ✓ It perfectly emphasizes the beauty of the natural wood pattern, giving it an aesthetic appearance.
- ✓ It effectively protects wood from the destructive effects of weather conditions.
- ✓ It creates a durable coating that effectively protects wood from dirt, moisture, UV radiation and biocorrosion.
- ✓ The waxes contained in the WOOD STAIN increase the resistance of the coating to abrasion and scratches.

SUBSTRATE PREPARATION:

- › The surface to be painted should be dry, clean, degreased and matted with sandpaper and then dust-free.
- › Wash greasy or resin-treated areas with extraction gasoline.
- › Raw wood should be seasoned (humidity max. 15%) and primed with a suitable primer.
- › In renovation painting, old peeling coatings for raw wood should be removed, any cavities and cracks should be filled with a suitable wood filler and after drying, sanded thoroughly with sandpaper.
- › In order to obtain proper adhesion of the WOOD STAIN, before applying the next layer, the surface should be sanded with fine-grained sandpaper and then dedusted.

HOW TO USE:

- › Mix the product thoroughly immediately before painting. Do not dilute.
- › Apply the first layer of the WOOD STAIN to the previously prepared surface with a brush, roller or spray, spreading thoroughly along the wood grain until an even layer is obtained and wait until the coating dries.
- › The drying time of the coating is about 1 hour and depends on the conditions at the place of application of the product (temperature and humidity).

TECHNICAL DATA SHEET

WOOD STAIN

- › Before applying the next layer, if the wood fibers rise, the coating should be sanded with fine-grained sandpaper and well removed from dust.
- › The third layer of the WOOD STAIN is recommended for surfaces particularly exposed to weather conditions.

ADDITIONAL INFORMATION:

- › The product is not recommended for painting wood species with a high content of tannins, such as oak and exotic woods.
- › Before applying the stain varnish on wood, it is recommended to carry out a colour test, as different types of wood may differ in absorption and final shade.
- › Optimal application conditions: temperature from +10°C to +30°C and relative humidity below 70%.
- › Initial surface protection after 24 hours. The coating is completely durable after 7 days, until then do not clean the painted surface, protect against water and dirt and mechanical damage.
- › Mild detergents should be used to care for the painted surface. Do not use rough sponges.
- › Wash the tools with water and detergent immediately after painting.

EFFICIENCY:

- › Up to 15 m²/l, depending on the method of application, and in particular on the type and species of painted wood. Efficiency given for one layer.

NUMBER OF LAYERS:

- › 2 to 3 layers, depending on the type of substrate and the desired effect.

SHELF LIFE:

- › 36 months from the date of production. Once opened, use within 6 months.

TRANSPORT AND STORAGE:

- › Store and transport in airtight, original packaging at a temperature of +5°C to +40°C. Protect from frost.

COMMENTS:

- › Keep out of reach of children. If swallowed, consult a doctor.
- › VOC content limit (cat. A/e/WB): 130 g/l. The product contains max. 130 g/l.
- › It contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction.
- › Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

The data contained in the technical data sheet is based on laboratory tests and practical experience and is communicated to the best of our knowledge in order to ensure optimal use of the product. These data are not the basis for the legal liability of the Manufacturer, as he has no influence and control over the conditions of use of the product. The manufacturer reserves the right to change the information contained in the card without prior notice to the Customer.